



00/60/00

03-10-00

Case Docket No.: 50N3545/1309

BOX PATENT APPLICATION
 ASSISTANT COMMISSIONER FOR PATENTS
 Washington, D.C. 20231

Sir:

Transmitted herewith for filing is the patent application of

Applicant(s): Bruce A. Fairman, Harold A. Ludtke, Scott D. Smyers and Glen D. Stone

 Title: Method For Utilizing Resource Characterizations To Optimize Performance
 In An Electronic Device

Enclosed are:

- ☒ 22 pages of specification, claims and abstract.
☒ 7 sheets of ☒ informal ☐ formal drawing(s).
☒ A declaration and power of attorney.
☒ An assignment transmittal.
☒ An assignment of the invention to: Sony Corporation, and Sony Electronics, Inc.
 Please record the assignment and return to the undersigned.
☐ A certified copy of a _____ application.
☐ An associate power of attorney.
☐ A verified statement to establish small entity status under 37 CFR §§ 1.9 and 1.27.
☐ PTO Form-1449 and copies of cited art.

The filing fee has been calculated as shown below:

For	(Col. 1) No. Filed	(Col. 2) No. Extra	Small Entity		or	Other Than a Small Entity	
			Rate	Fee		Rate	Fee
Basic Fee				\$380.00			\$690.00
Total Claims	42	22	x \$9 =	\$		x \$18 =	\$396.00
Indep. Claims	4	1	x \$39 =	\$	or	x \$78 =	\$78.00
Multiple Dependent Claims Present <input type="checkbox"/>			+ \$130 =	\$		+ \$260 =	\$
*If the difference in column 1 is less than zero, enter 0 in column 2			Total	\$	or	Total	\$1164.00

☐ Please charge my Deposit Account No. 06-0600 the amount of \$_____. **A duplicate copy of this sheet is enclosed.**
☒ A check in the amount of **\$1204.00** to cover the filing fee ☒ and recording of assignment is enclosed.

☒ The Commissioner is hereby authorized to charge payment of the following fees during the pendency of this application or credit any overpayment to Deposit Account No. 06-0600. **A duplicate copy of this sheet is enclosed.**
☒ Any additional filing fees required under 37 CFR § 1.16.

☒ Any patent application processing fees under 37 CFR § 1.17.

☐ The issue fee set in 37 CFR § 1.18 at or before mailing of the Notice of Allowance, pursuant to 37 CFR § 1.311(b).

Respectfully submitted,

Dated:

March 7, 2000

 Gregory J. Koerner, Registration No. 38,519
 Carr & Ferrell LLP
 2225 East Bayshore Road, Suite 200
 Palo Alto, California 94303
 Phone: (650) 812-3400
 FAX: (650) 812-3444

 jc525 U.S. PTO
 09/521308
 03/09/00

IN THE
UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICANT(S): Bruce A. Fairman, Harold A. Ludtke, Scott D. Smyers
and Glen D. Stone

FILING DATE: Unknown

SERIAL NO.: Unknown

TITLE: Method For Utilizing Resource Characterizations
To Optimize Performance In An Electronic Device

GROUP ART UNIT: Unknown

ATTY.DKT.NO.: 50N3545/1309

BOX PATENT APPLICATIONS
ASSISTANT COMMISSIONER FOR PATENTS
WASHINGTON, D.C. 20231

CERTIFICATE OF EXPRESS MAIL


SIR:

"Express Mail" mailing label number EL470300728US

Date of Deposit: March 9, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to:
Box Patent Application, Assistant Commissioner for Patents, Washington, D.C. 20231.

Deposited by: GREGORY KOERNER


(signature of person mailing application)

METHOD FOR UTILIZING RESOURCE CHARACTERIZATIONS TO OPTIMIZE PERFORMANCE IN AN ELECTRONIC DEVICE

CROSS-REFERENCE TO RELATED APPLICATIONS

5 This application is related to, and claims priority in, co-pending U.S. Provisional Patent Application Serial No. 60/161,206, entitled "Method For Implementing Scheduling Mechanisms By Utilizing Resource Characterizations," filed on October 21, 1999, and to co-pending U.S. Provisional Patent Application Serial No. 06/160,991, entitled "Method For
10 Quantifying Available System Resources Associated With A Hardware Component," filed on October 21, 1999. All of these related applications are commonly assigned, and are hereby incorporated by reference.

BACKGROUND SECTION

15

1. Field of the Invention

 This invention relates generally to techniques for implementing electronic devices, and relates more particularly to a method for utilizing
20 resource characterizations to optimize performance in an electronic device.

2. Description of the Background Art

 Implementing effective methods for utilizing device resources is a
25 significant consideration for designers and manufacturers of contemporary electronic devices. However, effectively utilizing device resources may create substantial challenges for designers of electronic devices. For example, enhanced demands for increased device functionality and performance may require more system processing power, bus bandwidth, and require
30 additional hardware resources. An increase in processing or hardware requirements may also result in a corresponding detrimental economic impact due to increased production costs and operational inefficiencies.

An electronic device in an electronic network may advantageously communicate with other electronic devices in the network to share resources to thereby substantially increase the capabilities and versatility of individual devices in the electronic network. For example, an electronic network may be
5 implemented in a home environment to enable flexible and beneficial sharing of data and device resources between various consumer electronic devices, such as personal computers, digital video disc (DVD) devices, digital set-top boxes for digital broadcasting, enhanced television sets, and audio reproduction systems.

10 Network size is also a factor that affects the management of resources in an electronic network. Communications in an electronic network typically become more complex as the number of individual devices or nodes increases. A local software module on the local device may need to communicate with various remote software elements on remote devices
15 across the electronic network. However, successfully managing resources of a substantial number of electronic devices across a network may provide significant benefits to a system user.

Furthermore, enhanced device capability to perform various advanced processes may provide additional benefits to a system user, but may also
20 place increased demands on the control and management of an electronic device. For example, an enhanced electronic device that effectively accesses, processes, and displays digital television programming may benefit from efficient use of resources because of the large amount and complexity of the digital data involved.

25 Due to growing demands on system resources and substantially increasing data magnitudes, it is apparent that developing new and effective methods for managing resources is a matter of importance for the related electronic technologies. Therefore, for all the foregoing reasons, implementing effective methods for utilizing resources remains a significant
30 consideration for designers, manufacturers, and users of contemporary electronic devices.

SUMMARY

In accordance with the present invention, a method is disclosed for effectively utilizing resource characterizations to optimize performance in an electronic device. In one embodiment of the present invention, initially, device software preferably generates an isochronous process request to a cantaloupe manager that functions as a resource allocation manager for the electronic device. In response, the cantaloupe manager preferably accesses resource usages or resource requirements that are listed in one or more resource characterizations known as "cantaloupes". The resource usages in an accessed cantaloupe preferably correspond to the foregoing isochronous process that was initially requested by the device software.

The cantaloupe manager then preferably may compare the resource usages from the cantaloupe(s) with currently-available resources of the electronic device. In certain embodiments, the cantaloupe manager may sequentially compare each individual resource usage from the cantaloupe with a corresponding current available resource of the electronic device.

If sufficient available resources are currently present for optimal performance of the requested isochronous process, then the cantaloupe manager preferably authorizes the device software to instantiate the requested process through a picokernel module. However, if sufficient currently-available resources are not present for optimal execution of the requested isochronous process, then the cantaloupe manager preferably generates a request-fail signal to the device software to thereby deny the request to instantiate the isochronous process.

In this manner, the present invention advantageously pre-allocates sufficient guaranteed resources for a given isochronous process, prior to instantiation, to thereby guarantee successful and deterministic performance of the requested isochronous process. The present invention therefore provides an effective method for utilizing resource characterizations to optimize performance in an electronic device.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram for one embodiment of an electronic network,
in accordance with the present invention;

5

FIG. 2 is a block diagram for one embodiment of an exemplary device of
FIG. 1, in accordance with the present invention;

FIG. 3 is a diagram for one embodiment of the memory of FIG. 2, in
10 accordance with the present invention;

FIG. 4 is a block diagram that illustrates non-optimal performance in
an electronic device;

15 FIG. 5 is a block diagram for one embodiment of a cantaloupe, in
accordance with the present invention;

FIG. 6 is a block diagram that illustrates a resource allocation
procedure, in accordance with one embodiment of the present invention; and

20

FIG. 7 is a flowchart of method steps for performing a resource
allocation procedure, in accordance with one embodiment of the present
invention.

DETAILED DESCRIPTION

The present invention relates to an improvement in electronic devices. The following description is presented to enable one of ordinary skill in the art to make and use the invention and is provided in the context of a patent application and its requirements. Various modifications to the preferred embodiment will be readily apparent to those skilled in the art and the generic principles herein may be applied to other embodiments. Thus, the present invention is not intended to be limited to the embodiment shown, but is to be accorded the widest scope consistent with the principles and features described herein.

A method for providing optimal performance in an electronic device is herein disclosed that comprises at least one resource characterization which includes resource requirements for executing a requested process. An allocation manager may then compare the resource requirements for the requested process and the currently-available device resources. The allocation manager may advantageously authorize or deny the requested process depending upon whether the currently-available resources are sufficient to adequately service the requested process.

Referring now to FIG. 1, a block diagram for one embodiment of an electronic network 110 is shown, in accordance with the present invention. In the FIG. 1 embodiment, network 110 preferably comprises, but is not limited to, a number of electronic devices 112 (device A 112(a), device B 112(b), root device 114, device C 112(c), device D 112(d), and device E 112(e)). In alternate embodiments, electronic network 110 may readily be configured to include various other devices or components that function in addition to, or instead of, those discussed in conjunction with the FIG. 1 embodiment. In alternate embodiments, network 110 may readily be connected and configured in any other appropriate and suitable manner.

In the FIG. 1 embodiment, devices 112 of network 110 may be implemented as any type of electronic device, including, but not limited to, personal computers, printers, digital video disc devices, television sets, audio systems, video cassette recorders, and set-top boxes for digital broadcasting.

5 In the FIG. 1 embodiment, devices 112 preferably communicate with one another using a network bus 132. Network bus 132 preferably includes path 132(a), path 132(b), path 132(c), path 132(d), and path 132(e). For example, in one embodiment, device B 112(b) is coupled to device A 112(a) via path 132(a), and to root device 114 via path 132(b). Similarly, root device 114 is
10 coupled to device C 112(c) via path 132(c), and to device D 112(d) via path 132(d). In addition, device D 112(d) is coupled to device E 112(e) via path 132(e). In the FIG. 1 embodiment, network bus 132 is preferably implemented using an IEEE Std 1394 Standard for a High Performance Serial Bus, which is hereby incorporated by reference. However, in alternate
15 embodiments, network 110 may readily communicate and function using various other network interconnectivity methodologies which are equally within the scope of the present invention.

In the FIG. 1 embodiment, each device in electronic network 110 may preferably communicate with any other device within network 110. For
20 example, device E 112(e) may communicate with device B 112(b) by transmitting transfer data via cable 132(e) to device D 112(d), which then may transmit the transfer data via cable 132(d) to root device 114. In response, root device 114 then may transmit the transfer data to device B 112(b) via cable 132(b). In the FIG. 1 embodiment, root device 114 preferably
25 provides a master cycle start signal to synchronize isochronous processes for devices 112 in network 110. In other embodiments of network 110, any one of the network devices 112 may be designated as the root device or cycle master.

30 Referring now to FIG. 2, a block diagram for one embodiment of an exemplary device 112 from network 110 is shown, in accordance with the present invention. Device 112 preferably includes, but is not limited to, a

processor 212, an input/output (I/O) interface 214, a memory 216, a device bus 226, and a bus interface 220. Processor 212, I/O interface 214, memory 216 and bus interface 220 preferably are each coupled to, and communicate via common device bus 226.

5 In the FIG. 2 embodiment, processor 212 may be implemented as any appropriate multipurpose microprocessor device. Memory 216 may be implemented as one or more appropriate storage devices, including, but not limited to, read-only memory, random-access memory, and various types of non-volatile memory, such as floppy disc devices or hard disc devices. I/O
10 interface 214 preferably may provide an interface for communications with various compatible sources and/or destinations.

In accordance with the present invention, bus interface 220 preferably provides an interface between device 112 and network 110. In the FIG. 2 embodiment, bus interface 220 preferably communicates with other devices
15 112 on network 110 via network bus 132. Bus interface 220 also preferably communicates with processor 212, I/O device 214, and memory 216 via a common device bus 226.

In the FIG. 2 embodiment, device 112 preferably includes the capability to perform various tasks that involve isochronous data and isochronous
20 processes. Isochronous data typically includes information that is time-sensitive, and therefore requires deterministic operations to guarantee delivery and processing of the isochronous data in a timely manner. For example, video data that is intended for immediate display must arrive at the appropriate destination in a time-synchronized manner in order to prevent
25 jitter or breakup of the corresponding image during display. To achieve this goal, device 112 preferably performs isochronous and other types of processing in segments of time called "cycles". Isochronous processes are synchronized with a cycle clock or submultiples thereof. Processes that are synchronized loosely with a sub-multiple of the cycle clock are called
30 plesiochronous processes.

Scheduling of isochronous processes typically requires a finite time period that is sometimes referred to as "overhead". As the cycle time period is

reduced, the overhead becomes a more significant factor because of the reduced amount of time remaining to perform the actual isochronous transfer. In the FIG. 2 embodiment, the cycle time period may be in the proximity of 125 microseconds, with a cycle frequency of approximately eight
5 kilohertz.

Referring now to FIG. 3, a diagram for one embodiment of the FIG. 2 memory 216 is shown, in accordance with the present invention. In the FIG. 3 embodiment, memory 216 preferably includes, but is not limited to, device
10 software 312, picokernel 314, cantaloupe manager 316, cantaloupe(s) 318, and resource values 320. In alternate embodiments, memory 216 may readily include various other components in addition to, or instead of, the components that are discussed in conjunction with the FIG. 3 embodiment.

In the FIG. 3 embodiment, device software 312 includes software
15 instructions that are preferably executed by processor 212 for performing various functions and operations by device 112. The particular nature and functionality of device software 312 preferably varies depending upon factors such as the type and purpose of the corresponding host device 112.

In the FIG. 3 embodiment, picokernel 312 preferably controls and
20 coordinates the scheduling of isochronous processes by utilizing an optimized process representation to reduce the cost or overhead of scheduling to a minimum. Cantaloupe manager 316 preferably includes an allocation manager that may utilize information from cantaloupe(s) 318 to determine whether a particular isochronous process may be instantiated on behalf of
25 another entity, such as device software 312. Cantaloupe(s) 318 preferably comprise a resource characterization that includes one or more characterizations of hardware and/or software resources necessary to meet performance criteria for a particular isochronous process. Cantaloupe(s) 318 are further discussed below in conjunction with FIGS. 5 through 7.

30 Resource values 320 preferably include any relevant information regarding current resource availability and allocations in device 112. For example, in the FIG. 3 embodiment, resource values 320 may include one or

more available resource value(s), one or more allocated resource value(s), and one or more total device resource value(s) for device 112. In the FIG. 3 embodiment, prior to allocation of any resources, the available resource value(s) may initially be set to a value that is less than 100% of total device resource values (such as 75%) to thereby reserve resources necessary for non-isochronous processes or system tasks.

Referring now to FIG. 4, a block diagram that illustrates non-optimal performance in an exemplary electronic device 412 is shown. In the FIG. 4 embodiment, device 412 preferably instantiates a process A 424 that is performed using software 416 and hardware 420. For example, process A 424 may consume 75% of the total resources available on device 412 to decode and display video programming. In the FIG. 4 embodiment, device 412 then preferably instantiates a process B 430 that is performed using software 416 and hardware 420. For example, process B 430 may require 35% of the total resources available on device 412 to perform a speech recognition function.

Simultaneously executing process A 424 (using 75% of total available resources) and process B 430 (using 35% of total available resources) requires more than 100% of the total resources available from device 412 ($75\% + 35\% = 110\%$). Therefore, insufficient resources are available for simultaneously executing process A 424 and process B 430. Device 412 may attempt to simultaneously execute process A 424 and process B 430 by reducing the amount of resources provided to one or both of the simultaneously-executing processes.

Executing a particular process without providing sufficient resources may result in non-optimal performance or “graceful degradation”. For example, if process A 424 lacks sufficient resources for successful performance, such graceful degradation may include the disruption of video information that is being displayed to a system viewer. In many circumstances, such degradation of device performance is not desirable or acceptable as a performance model for many electronic devices.

Referring now to FIG. 5, a diagram for one embodiment of a cantaloupe 318 is shown, in accordance with the present invention. In the FIG. 5 embodiment, cantaloupe 318 preferably includes a listing for a resource 1 (512(a)) through a listing for a resource N (512(c)). In the FIG. 5 embodiment, resources 512 may include any appropriate aspects of devices 112 or network 110 (FIG. 1). For example, resource 512 may correspond to the bandwidth for a particular bus, such as device bus 226 or network bus 132. Similarly, resource 512 may correspond to the processing capacity for a central processing device, such as processor 212 (FIG. 2), or to the capacity of a memory device, such as memory 216. In alternate embodiments of the present invention, cantaloupe 318 may readily be implemented to include various other configurations, and may also include various items and components that are different from those discussed in conjunction with the FIG. 5 embodiment.

In accordance with the present invention, cantaloupe 318 is preferably associated with a particular time-sensitive isochronous or plesiochronous process on network 110. Prior to instantiating the foregoing process, cantaloupe manager 316 may then advantageously reference cantaloupe 318 to determine the individual and total resources necessary for the associated process. Determining in advance whether sufficient system resources are available for successful operation of a given process ensures that the associated isochronous process is guaranteed sufficient resources for timely and deterministic performance. Providing sufficient resources becomes more significant as the cycle duration decreases and the cycle frequency increases. In one embodiment of the present invention, the cycle period may preferably be in the proximity of 125 microseconds, with a rate of eight kilohertz.

In the FIG. 5 embodiment, cantaloupe 318 preferably also includes a listing for a resource 1 usage (514(a)) through a listing for a resource N usage (514(c)). In the FIG. 5 embodiment, each of resource usages 514 preferably corresponds with a given resource 512 to characterize the amount of the

given resource 512 required by the isochronous process associated with cantaloupe 318.

For example, if a given resource 512 is the bandwidth for a particular bus, then the corresponding resource usage 514 may be expressed in bandwidth units utilized by a process. Similarly, if a given resource 512 is the processing capacity for a central processing device, then corresponding resource usage 514 may be expressed in CPU units, such as machine-instructions per second (MIPS). In various embodiments of the present invention, resource usages 514 may be implemented in any appropriate and compatible format for use by network 110. In one embodiment, cantaloupe 318 may be implemented using only resource usages 514, with the corresponding resources 512 indirectly implied and understood during instantiation of process on network 110. In certain embodiments, cantaloupe 318 may also be utilized to characterize other resources, such as the total system resources, or the current available resources of device 112.

Therefore, cantaloupe 318 preferably includes an at least two-dimensional array of descriptive parameters. The first parameter preferably may be the type of resource being characterized, and the second parameter is the amount of required resource usage. A cantaloupe 318 may thus serve as a common descriptor to couple hardware and software scheduling mechanisms by describing resource requirements. For example, resource usage may be characterized and described as a ratio of the amount of usage per a given time period (including process scheduling overhead).

Referring now to FIG. 6, a block diagram illustrating the use of cantaloupe 318 is shown, in accordance with one embodiment of the present invention. In alternate embodiments, cantaloupe 318 may readily be utilized in various other manners and configurations, in accordance with the present invention.

In the FIG. 6 embodiment, device software 312 initially generates an isochronous process request to cantaloupe manager 316 via path 618. In response, cantaloupe manager 316 preferably accesses the resource usages

514 in cantaloupe 318 via path 614. In the FIG. 6 embodiment, cantaloupe 318 preferably corresponds to the foregoing isochronous process that was initially requested by device software 312.

Cantaloupe manager 316 then preferably compares the resource usages 514 from cantaloupe 318 with available resources 320 for the requested process via path 616. In the FIG. 6 embodiment, cantaloupe manager 316 may sequentially compare each individual resource usage 514 from cantaloupe 318 with a corresponding currently-available associated system resource 320.

If sufficient additional current resources 512 are available for the requested isochronous process, then cantaloupe manager 316 preferably authorizes device software 312 to schedule and instantiate the requested process through picokernel 314. However, if sufficient current resources 512 are not available for the requested isochronous process, then cantaloupe manager 316 preferably generates a request fail signal to device software 312 to deny authorization of the requested isochronous process. In this manner, the present invention advantageously pre-allocates sufficient resources for a given isochronous process, prior to instantiation, to thereby guarantee successful and deterministic performance of the isochronous process.

Referring now to FIG. 7, a flowchart of method steps for performing a resource allocation procedure is shown, in accordance with one embodiment of the present invention. In alternate embodiments, the FIG. 7 resource allocation procedure may readily be performed in various other manners and sequences, in accordance with the present invention.

In the FIG. 7 embodiment, initially, in step 712, an entity (such as device software 312) preferably generates a request for instantiation of an isochronous process. In response, in step 716, cantaloupe manager 316 preferably examines one or more cantaloupes 318 that correspond to the requested isochronous process.

In step 720, cantaloupe manager 316 preferably determines whether sufficient resources are currently available for performing the requested

isochronous process. In accordance with the present invention, cantaloupe manager 316 may utilize any appropriate technique to determine whether sufficient resources are available for performing the requested process.

In the FIG. 7 embodiment, cantaloupe manager 316 preferably
5 maintains one or more available resource values in resource values 320 of memory 216 (FIG. 3) to quantitatively represent any currently unallocated resources. For example, available resource values may be expressed as percentages of total system resources, or as a finite resource amount. Cantaloupe manager 316 may then compare the resources required for the
10 requested process (obtained from cantaloupe(s) 318) and the currently-available resource value(s) to determine whether sufficient unallocated resources are available for utilization by the requested process.

In step 720, if cantaloupe manager 316 determines that sufficient resources are not available for performing the requested process, then, in
15 step 724, cantaloupe manager 316 preferably denies the request for instantiation of the process, and the FIG. 7 method terminates. However, if cantaloupe manager 316 determines that sufficient resources are available for performing the requested process, then, in step 728, cantaloupe manager 316 preferably allocates the required resources, and thereby allows granting
20 of the request for instantiation of the isochronous process.

In step 732, cantaloupe manager 316 preferably updates the available resource value(s) in memory 216 to exclude the resources that were allocated in foregoing step 728 to service the requested isochronous process. For example, if the requested process requires twenty-five percent of the managed
25 resources, then, cantaloupe manager 316 preferably may decrease the available resource value in memory 216 by twenty-five percent. Finally, in step 736, picokernel 314 of device 112 preferably may instantiate and execute the requested isochronous process. The resources that are allocated for the isochronous process are therefore guaranteed to be available, and the
30 isochronous process is thus assured of successful execution without degraded or non-optimal performance. In accordance with the present

invention, the FIG. 7 process may readily be utilized to evaluate a series of requested isochronous processes.

The invention has been explained above with reference to a preferred
5 embodiment. Other embodiments will be apparent to those skilled in the art
in light of this disclosure. For example, the present invention may readily be
implemented using configurations and techniques other than those described
in the preferred embodiment above. Additionally, the present invention may
effectively be used in conjunction with systems other than the one described
10 above as the preferred embodiment. Therefore, these and other variations
upon the preferred embodiments are intended to be covered by the present
invention, which is limited only by the appended claims.

WHAT IS CLAIMED IS:

1. A system for effectively utilizing resources in an electronic device, comprising:

5 a resource characterization coupled to said electronic device, said
resource characterization corresponding to a requested process;
an allocation manager configured to handle said requested process by
referencing said resource characterization; and
a processor coupled to said electronic device for controlling said
10 allocation manager.

2. The system of claim 1, wherein said electronic device is coupled to an
electronic network that is implemented according to an IEEE Std 1394 serial
bus standard.

15 3. The system of claim 1 wherein said electronic device is one of a
consumer-electronics device, an audio-visual device, a set-top box, and a
personal computer device.

20 4. The system of claim 1 wherein said requested process includes one or
more time-sensitive isochronous processes for manipulating time-critical
isochronous data.

5. The system of claim 1 wherein said resource characterization includes
25 resource requirements for executing said requested process, and wherein
said allocation manager compares said resource requirements to current
available resources, said allocation manager authorizing said requested
process only when said resource requirements are less than, or equal to, said
current available resources.

30

6. The system of claim 1 wherein a software module generates a request to instantiate said requested process on said electronic device.

7. The system of claim 6 wherein said request includes an identifier that corresponds to said resource characterization.

8. The system of claim 6 wherein said allocation manager evaluates said resource characterization in response to said request from said software module.

10

9. The system of claim 8 wherein said resource characterization includes one or more resource listings and one or more corresponding resource usage values that are required for an optimal performance of said requested process.

15

10. The system of claim 8 wherein said resource characterization includes resource information regarding total available resources from said electronic device.

20

11. The system of claim 8 wherein said allocation manager compares resource usage values from said resource characterization and current available resource values from said electronic device to determine whether to authorize said requested process.

25

12. The system of claim 11 wherein said current available resource values are initially set to be less than one-hundred percent of total device resources before any resource allocation is made.

30

13. The system of claim 11 wherein said allocation manager authorizes said requested process whenever said resource usage values from said resource characterization are less than or equal to said current available resource values from said electronic device.

14. The system of claim 11 wherein said allocation manager denies said requested process whenever said resource usage values from said resource characterization are greater than said current available resource values from
5 said electronic device.

15. The system of claim 13 wherein said allocation manager updates said available resource values with said resource usage values whenever said requested process is authorized by said allocation manager.

10

16. The system of claim 13 wherein a picokernel in said electronic device instantiates and executes said requested process after said allocation manager authorizes said requested process.

15 17. The system of claim 16 wherein said requested process executes with optimal performance due to guaranteed pre-allocated resources provided by said electronic device.

18. The system of claim 1 wherein said allocation manager sequentially
20 references a plurality of resource characterizations to handle a plurality of respective requested processes.

19. The system of claim 1 wherein said allocation manager references a plurality of resource characterizations to handle said requested process.

25

20. The system of claim 1 wherein at least one of said resource characterization and said allocation manager is re-configurable to provide an altered functionality to said electronic device.

30

21. A method for effectively utilizing resources in an electronic device, comprising the steps of:

referencing a resource characterization with an allocation manager,
said resource characterization corresponding to a requested
process;

handling said requested process with said allocation manager based
upon said resource characterization; and

controlling said allocation manager with a processor that is coupled to
said electronic device.

22. The method of claim 21, wherein said electronic device is coupled to an
electronic network that is implemented according to an IEEE Std 1394 serial
bus standard.

23. The method of claim 21 wherein said electronic device is one of a
consumer-electronics device, an audio-visual device, a set-top box, and a
personal computer device.

24. The method of claim 21 wherein said requested process includes one
or more time-sensitive isochronous processes for manipulating time-critical
isochronous data.

25. The method of claim 21 wherein said resource characterization
includes resource requirements for executing said requested process, and
wherein said allocation manager compares said resource requirements to
current available resources, said allocation manager authorizing said
requested process only when said resource requirements are less than, or
equal to, said current available resources.

26. The method of claim 21 wherein a software module generates a request to instantiate said requested process on said electronic device.

27. The method of claim 26 wherein said request includes an identifier that
5 corresponds to said resource characterization.

28. The method of claim 26 wherein said allocation manager evaluates said resource characterization in response to said request from said software module.

10

29. The method of claim 28 wherein said resource characterization includes one or more resource listings and one or more corresponding resource usage values that are required for an optimal performance of said requested process.

15

30. The method of claim 28 wherein said resource characterization includes resource information regarding total available resources from said electronic device.

20 31. The method of claim 28 wherein said allocation manager compares resource usage values from said resource characterization and current available resource values from said electronic device to determine whether to authorize said requested process.

25 32. The method of claim 31 wherein said current available resource values are initially set to be less than one-hundred percent of total device resources before any resource allocation is made.

30 33. The method of claim 31 wherein said allocation manager authorizes said requested process whenever said resource usage values from said resource characterization are less than or equal to said current available resource values from said electronic device.

34. The method of claim 31 wherein said allocation manager denies said requested process whenever said resource usage values from said resource characterization are greater than said current available resource values from
5 said electronic device.

35. The method of claim 33 wherein said allocation manager updates said available resource values with said resource usage values whenever said requested process is authorized by said allocation manager.

10

36. The method of claim 33 wherein a picokernel in said electronic device instantiates and executes said requested process after said allocation manager authorizes said requested process.

15 37. The method of claim 36 wherein said requested process executes with optimal performance due to guaranteed pre-allocated resources provided by said electronic device.

38. The method of claim 21 wherein said allocation manager sequentially
20 references a plurality of resource characterizations to handle a plurality of respective requested processes.

39. The method of claim 21 wherein said allocation manager references a plurality of resource characterizations to handle said requested process.

25

40. The method of claim 21 wherein at least one of said resource characterization and said allocation manager is re-configurable to provide an altered functionality to said electronic device.

30

41. A computer-readable medium comprising program instructions for utilizing resources in an electronic device by performing the steps of:

referencing a resource characterization with an allocation manager,
said resource characterization corresponding to a requested
process;

handling said requested process with said allocation manager based
upon said resource characterization; and

controlling said allocation manager with a processor that is coupled to
said electronic device.

42. A system for effectively utilizing resources in an electronic device,
comprising:

means for referencing a resource characterization that corresponds to a
requested process;

means for handling said requested process based upon said resource
characterization; and

means for controlling said means for referencing and said means for
handling.

METHOD FOR UTILIZING RESOURCE CHARACTERIZATIONS
TO OPTIMIZE PERFORMANCE IN AN ELECTRONIC DEVICE

5

ABSTRACT OF THE DISCLOSURE

A method for providing optimal performance in an electronic device comprises at least one resource characterization that includes resource requirements for executing a requested process. An allocation manager may
10 then compare the resource requirements for the requested process to the currently-available device resources. The allocation manager may then authorize or deny the requested process depending upon whether the currently-available resources are sufficient to adequately service the resource requirements of the requested process.

15

FIG. 1 is a block diagram of a system 110, according to one embodiment. The system 110 includes a Root Device 114, which is connected to Device A 112(a), Device B 112(b), Device C 112(c), Device D 112(d), and Device E 112(e). The Root Device 114 is also connected to Device A 112(a) via a connection 132(a), to Device B 112(b) via a connection 132(b), to Device C 112(c) via a connection 132(c), to Device D 112(d) via a connection 132(d), and to Device E 112(e) via a connection 132(e).




Fig. 1





Fig. 2



216

Fig. 3




FIG. 4


318

FIG. 5




FIG. 6




FIG. 7

DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am an original, first and joint inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled:

**"Method For Utilizing Resource Characterizations
To Optimize Performance In An Electronic Device"**

the specification of which:

☒ is attached hereto.

☐ was filed on _____ as U.S. Application No.
or PCT International Application No. _____
and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code §119(a)-(d) or §365(b) of any foreign application(s) for patent or inventor's certificate, or §365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below any foreign application for patent or inventor's certificate, or PCT International application, having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)

Priority Claimed

_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	<input type="checkbox"/> Yes	<input type="checkbox"/> No
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	<input type="checkbox"/> Yes	<input type="checkbox"/> No

I hereby claim the benefit under Title 35, United States Code §119(e) of any United States provisional application(s) listed below.

<u>60/161,206</u>	<u>October 21, 1999</u>
(Application Number)	(Filing Date)
<u>60/160,991</u>	<u>October 21, 1999</u>
(Application Number)	(Filing Date)

I hereby claim the benefit under Title 35, United States Code §120 of any United States application(s), or §365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code §112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, §1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application.

<u>(Application Number)</u>	<u>(Filing Date)</u>	<u>(Status -- patented, pending, abandoned)</u>
<u>(Application Number)</u>	<u>(Filing Date)</u>	<u>(Status -- patented, pending, abandoned)</u>

POWER OF ATTORNEY: I hereby appoint the following attorneys to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

John S. Ferrell, Reg. No. 34,593; Gregory J. Koerner, Reg. No. 38,519
J. Eppa Hite, Reg. No. 30,266; Charles B. Katz, Reg. No. 36,564;
Robert D. Wasson, Reg. No. 40,218; Susan Yee, Reg. No. 41,388;
and Wendi R. Schepler, Reg. No. 43,091

SEND ALL CORRESPONDENCE TO:

Gregory J. Koerner, Reg. No. 38,519
CARR & FERRELL LLP
2225 East Bayshore Road, Suite 200
Palo Alto, CA 94303
TEL: (650) 812-3400
FAX: (650) 812-3444

1970	1971	1972	1973	1974	1975
1976	1977	1978	1979	1980	1981
1982	1983	1984	1985	1986	1987
1988	1989	1990	1991	1992	1993
1994	1995	1996	1997	1998	1999
2000	2001	2002	2003	2004	2005
2006	2007	2008	2009	2010	2011
2012	2013	2014	2015	2016	2017
2018	2019	2020	2021	2022	2023
2024	2025	2026	2027	2028	2029
2030	2031	2032	2033	2034	2035
2036	2037	2038	2039	2040	2041
2042	2043	2044	2045	2046	2047
2048	2049	2050	2051	2052	2053
2054	2055	2056	2057	2058	2059
2060	2061	2062	2063	2064	2065
2066	2067	2068	2069	2070	2071
2072	2073	2074	2075	2076	2077
2078	2079	2080	2081	2082	2083
2084	2085	2086	2087	2088	2089
2090	2091	2092	2093	2094	2095
2096	2097	2098	2099	2100	2101
2102	2103	2104	2105	2106	2107
2108	2109	2110	2111	2112	2113
2114	2115	2116	2117	2118	2119
2120	2121	2122	2123	2124	2125
2126	2127	2128	2129	2130	2131
2132	2133	2134	2135	2136	2137
2138	2139	2140	2141	2142	2143
2144	2145	2146	2147	2148	2149
2150	2151	2152	2153	2154	2155
2156	2157	2158	2159	2160	2161
2162	2163	2164	2165	2166	2167
2168	2169	2170	2171	2172	2173
2174	2175	2176	2177	2178	2179
2180	2181	2182	2183	2184	2185
2186	2187	2188	2189	2190	2191
2192	2193	2194	2195	2196	2197
2198	2199	2200	2201	2202	2203
2204	2205	2206	2207	2208	2209
2210	2211	2212	2213	2214	2215
2216	2217	2218	2219	2220	2221
2222	2223	2224	2225	2226	2227
2228	2229	2230	2231	2232	2233
2234	2235	2236	2237	2238	2239
2240	2241	2242	2243	2244	2245
2246	2247	2248	2249	2250	2251
2252	2253	2254	2255	2256	2257
2258	2259	2260	2261	2262	2263
2264	2265	2266	2267	2268	2269
2270	2271	2272	2273	2274	2275
2276	2277	2278	2279	2280	2281
2282	2283	2284	2285	2286	2287
2288	2289	2290	2291	2292	2293
2294	2295	2296	2297	2298	2299
2300	2301	2302	2303	2304	2305
2306	2307	2308	2309	2310	2311
2312	2313	2314	2315	2316	2317
2318	2319	2320	2321	2322	2323
2324	2325	2326	2327	2328	2329
2330	2331	2332	2333	2334	2335
2336	2337	2338	2339	2340	2341
2342	2343	2344	2345	2346	2347
2348	2349	2350	2351	2352	2353
2354	2355	2356	2357	2358	2359
2360	2361	2362	2363	2364	2365
2366	2367	2368	2369	2370	2371
2372	2373	2374	2375	2376	2377
2378	2379	2380	2381	2382	2383
2384	2385				

Inventor's signature: Bruce A. Jansma Dated: 23 FEB 2000

Post Office Address: same Citizenship: United States

Inventor's signature: *[Signature]* Dated: 2/28/00

Post Office Address: same Citizenship: United States

Inventor's signature: Harold C. Jolly Dated: 2/28/00

Post Office Address: same Citizenship: United States

Inventor's signature:  Dated: 2/28/00

Post Office Address: same Citizenship: United States